



US 20160029825A1

(19) **United States**(12) **Patent Application Publication**
Perrin(10) **Pub. No.: US 2016/0029825 A1**(43) **Pub. Date: Feb. 4, 2016**(54) **GARMENT SEPARATOR**(71) Applicant: **Stacy Elizabeth Perrin**, Boynton Beach,
FL (US)(72) Inventor: **Stacy Elizabeth Perrin**, Boynton Beach,
FL (US)(21) Appl. No.: **14/612,932**(22) Filed: **Feb. 3, 2015****Related U.S. Application Data**(63) Continuation-in-part of application No. 14/445,507,
filed on Jul. 29, 2014.**Publication Classification**(51) **Int. Cl.**

<i>A47G 25/14</i>	(2006.01)
<i>F16B 2/10</i>	(2006.01)
<i>A47B 61/00</i>	(2006.01)
<i>F16B 1/00</i>	(2006.01)
<i>F16B 2/00</i>	(2006.01)

(52) **U.S. Cl.**CPC *A47G 25/1471* (2013.01); *F16B 1/00*
(2013.01); *F16B 2/005* (2013.01); *A47B*
61/003 (2013.01); *F16B 2/10* (2013.01); *F16B*
2001/0035 (2013.01)

(57)

ABSTRACT

A garment separator assembly is provided including at least two separators. Each separator includes a first member defining a first half of the separator; and a second member defining an opposing second half of the separator. The second member is coupled to the first member and, together with the first member, defines a first inner-surface circumference and a second inner-surface circumference adjacent and non-coaxial with the first inner-surface circumference. The first inner-surface circumference is larger than the second inner-surface circumference. The first inner-surface circumference is shaped and sized to mate with a first outer diameter of a standard clothing rod; and the second inner-surface circumference is shaped and sized to mate with a second outer diameter of a clothing rod, wherein the second outer diameter is smaller than the first outer diameter of the standard clothing rod.

